



Enterprise-Grade Internet Service

LTE Routers
Cellular Service
Enterprise Management Platform
App for Individual Use



Connect

Your devices to the internet over cellular & fixed wired line, instantly



Protect

Your home, small business, boat, or RV with built-in cellular back-up and advanced security features



Control

Your network from anywhere with Simplifi's native app and cloud-based remote management platform

Be resilient in work & play:

Far more than a hotspot Simplifi, has all your home and small business connectivity needs covered.



Resiliency
Built in fail-over so you never lose connection again!



Security
IPsec, UAM/RADIUS, SPI/Firewall, port forwarding, cellular to ethernet connection



Connected
Complete network in a box. 32 WiFi Connections, connected to fixed wire line and/or LTE, 4G, 3G, 2G



Simplicity
Plug n' play, set and forget. Remote management platform for easy configuration



Portability
No moving parts, no external antennas, works anywhere there is cellular connection



Reliable
24 hour support, Enterprise grade solution

Ready to join The Resiliency?

Contact

Sales@Simplifi.io
239-919-8551

Networks

BS6425L-A-11
LTE FDD: B2/B4/B12
WCDMA: B2/B4/B5

BS6425L-AF-11
LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71
WCDMA: B2/B4/B5

BS6425L-AU-11
LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28
LTE TDD: B40
WCDMA: B1/B2/B5/B8
GSM: B2/B3/B5/B8

BS6425L-E-11
LTE FDD: B1/B3/B5/B7/B8/B20
LTE TDD: B38/B40/B41
WCDMA: B1/B5/B8
GSM: B3/B8

BS6425L-G-11
LTE FDD: B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20
B25/B26/B28
LTE TDD: B38/B39/B40/B41
WCDMA: B1/B2/B4/B5/B6/B8/B19
GSM: B2/B3/B5/B8

BS6425L-V-11
LTE FDD: B4/B13

Data Speeds

LTE - FDD CAT4 Max 150Mbps (DL), Max 50Mbps (UL)
DC-HSPA+ DL 42 Mbps
HSUPA - UL 5.76Mbps

WLAN

Dual-Band/ 802.11 b/g/n/ac, WPA / WPA2/WPA2 Enterprise

USB (3.0)

USB (Host) HS and FS

LAN

(10/100/1000 Base-T)

RJ-45 Modular Jack on side panel for TCP / IP, PPP, UDP

SIM

1.8V and 3.0V standard USIM (2FF)

LED Indicators

Cellular network status (1 ea.)
LAN traffic (1 ea.)
USB traffic (1 ea.)

Power Supply Requirements

120/240 VAC at 10VA (10W) max

Outline Dimensions

(Less AC prongs and mounting tab)

4.1" (104mm) Height
2.2" (56mm) Width
2.0" (51mm) Depth

Weight

7 oz (198 g)

Operating Temperature

-10°C to +40°C

Storage Temperature

-30°C to +70°C

Approvals

PTCRB, 3GPP
FCC parts 2 and 15
CE, TUV